

BIO CLEAN 6" DIA DOWNSPOUT FILTER – Screen Type

PATENTED
AND PATENTS PENDING

.83 SQ FT FILTER
SURFACE AREA

TREATMENT FLOW RATE
= .56 CFS

BYPASS FLOW RATE
= 1.26 CFS

FILTER INSERT
Stainless Steel

FILTER SCREEN

BioSorb HYDROCARBON BOOM

FILTER HOUSING
O.D. 6⁵/₈"

HANDLES

12³/₁₆"
TOTAL
HEIGHT

HIGH FLOW
BYPASS

For Model#
BC-DF2

2" LISTED
ADAPTER

4" LISTED
ADAPTER

For Model#
BC-DF4

NOTES

1. The device shall be sized according to the nominal size of the interconnecting drainage system. At no time shall the entrance size be larger than the exit size.
2. The device shall be installed in an accessible location to provide for means of repair and maintenance.
3. The device shall be installed using approved adapters or couplings to attach the device to the downspout or drainage pipe.
4. Screens are made out of 46 mesh stainless steel. 0.0055in. wire diameters. 55% open around exterior of filter insert.



BIO CLEAN ENVIRONMENTAL PO BOX 869, OCEANSIDE, CA P 760.433.7640 F 760.433.3179		PROJECT:	
6" DOWNSPOUT FILTER SCREEN TYPE MODEL NO. BC-DF2, BC-DF4		DRAWING #:	
DATE: 9/6/2012		REVISIONS: LM	DATE: 9/6/2012
DRAFTER: T.H.H.		REVISIONS:	DATE:
SCALE: NTS		UNITS = INCHES	